

ADAM-3011 ADAM-3013 ADAM-3014

Isolated Thermocouple Input Module

Isolated RTD Input Module

Isolated DC Input/Output Module



ADAM-3011



ADAM-3013



ADAM-3014



Specifications

Thermocouple Input

- **Common Mode Rejection** 115 dB min
- **Input Type**

T/C type	Temperature Range (° C)	Accuracy at 25° C (° C)
J	-40 ~ 760	±2
K	0 ~ 1,000	±2
T	-100 ~ 400	±2
E	0 ~ 1,000	±2
S	500 ~ 1,750	±4
R	500 ~ 1,750	±4
B	500 ~ 1,800	±4

- **Isolation (Three-way)** 1,000 V_{DC}
- **Output Impedance** 0.5 Ω
- **Stability (Temperature Drift)** ±2° C
- **Voltage Output** 0 ~ 10 V

General

- **Certifications** CE, FM
- **Connectors** Screw terminal
- **Enclosure** ABS
- **Indicators** Power LED indicator
- **Isolation** 1,000 V_{DC}
- **Power Consumption** 1.4 W
- **Power Input** +24 V_{DC} ± 10%
- **Operating Temperature** 0 ~ 50° C (32 ~ 122° F)
- **Storage Temperature** -25 ~ 85° C (-13 ~ 185° F)

Ordering Information

- **ADAM-3011** Isolated Thermocouple Input Module

Specifications

RTD Input

- **Accuracy** ± 0.1% of full range (voltage) or +/- 0.15° C (voltage)
± 0.2% of full range (current)
- **Bandwidth** 4 Hz
- **Input CMR at DC** 92 dB min.
- **Input Connections** 2, 3 or 4 wires
- **Input Type**

RTD type	α	Temperature Range (° C)
Pt	0.00385	-100 ~ 100
Pt	0.00385	0 ~ 100
Pt	0.00385	0 ~ 200
Pt	0.00385	0 ~ 600
Pt	0.00385	-100 ~ 0
Pt	0.00385	-100 ~ 200
Pt	0.00385	-50 ~ 50
Pt	0.00385	-50 ~ 150
Pt	0.00392	-100 ~ 100
Pt	0.00392	0 ~ 100
Pt	0.00392	0 ~ 200
Pt	0.00392	0 ~ 600
Ni	N/A	0 ~ 100
Ni	N/A	-80 ~ 100

- **Output Range** 0 ~ 5 V, 0 ~ 10 V, 0 ~ 20 mA
- **Output Resistance** < 5 Ω
- **Temperature Drift** ± 30 ppm of full range

General

- **Certifications** CE, FM
- **Connectors** Screw terminal
- **Enclosure** ABS
- **Indicators** Power LED indicator
- **Isolation** 1,000 V_{DC}
- **Power Consumption** < 0.95 W
- **Power Input** 24 V_{DC} ± 10%
- **Operating Temperature** 0 ~ 70° C (32 ~ 158° F)
- **Storage Temperature** -25 ~ 85° C (-13 ~ 185° F)

Ordering Information

- **ADAM-3013** Isolated RTD Input Module

Specifications

I/O

- **Accuracy** ±0.1% of full range (typical)
- **Common Mode Rejection** > 100 dB @ 50 Hz/60 Hz
- **Current Input** Bipolar: ±20 mA
Unipolar: 0 ~ 20 mA
Input impedance: 250 Ω
- **Current Output** 0 ~ 20 mA
- **Stability (Temperature Drift)** 150 ppm (typical)
- **Voltage Input** Bipolar input: ±10 mV, ±50 mV, ±100 mV, ±0.5 V, ±1.0 V, ±5 V, ±10 V
Unipolar input: 0 ~ 10 mV, 0 ~ 50 mV, 0 ~ 100 mV, 0 ~ 0.5 V, 0 ~ 1 V, 0 ~ 5 V, 0 ~ 10 V
Input impedance: 2 MΩ
Input bandwidth: 2.4 kHz (typical)
- **Voltage Output** Bipolar: ±5 V, ±10 V
Unipolar: 0 ~ 10 V
Impedance: < 50 Ω
Drive: 10 mA max.

General

- **Certifications** CE, FM
- **Connectors** Screw terminal
- **Enclosure** ABS
- **Indicators** Power LED indicator
- **Isolation (Three-way)** 1,000 V_{DC}
- **Power Consumption** 0.85 W (voltage output)
1.2 W (current output)
- **Power Input** 24 V_{DC} ± 10%
- **Operating Temperature** -10 ~ 70° C (14 ~ 158° F)
- **Storage Temperature** -25 ~ 85° C (-13 ~ 185° F)

Ordering Information

- **ADAM-3014** Isolated DC Input/Output Module